

Description

Thread Size: 1/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	EN1282ND6
Minimum Qty (MOQ):	5
NSN:	5320-01-490-9746
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

A circular placeholder with a thin grey border containing the text "NO IMAGE AVAILABLE" in all caps.

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N EN1282ND6 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.348 Inches Minimum And 0.376 Inches Maximum
Collar Overall Height:	0.295 Inches Nominal
Lubrication:	Dry Film Or Cetyl Alcohol
Collar Inside Diameter:	0.206 Inches Minimum And 0.212 Inches Maximum
End Item Identification:	F-22; Global Hawk, Rq-4a
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.1900 Inches
Collar Style:	Threaded (break Off) Type
Material:	Titanium Alloy Overall
Material Document And Classification:	Mil-t-9047 Mil Spec Single Material Response Collar
Material Document And Classification:	Mil-t-9046 Mil Spec Single Material Response Washer
Surface Treatment Document And Classification:	As5272, Type 1 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this nut from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/EN1282ND6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.