

**Description**

Fastener Length: 1-3/8", Hole Diameter: 1/32", Thread: 1/4-28, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | EWB04204H14                               |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-00-508-9224                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N EWB0420-4H14 Specifications

|                                   |   |
|-----------------------------------|---|
| <b>Thread Class:</b>              | 3a  |
| <b>Thread Direction:</b>          | Right-hand                                      |
| <b>Thread Length:</b>             | 0.462 Inches Minimum And 0.512 Inches Maximum   |
| <b>Fastener Length:</b>           | 1.347 Inches Minimum And 1.377 Inches Maximum   |
| <b>Head Style:</b>                | Double Hexagon W/hole                           |
| <b>Head Height:</b>               | 0.290 Inches Minimum And 0.310 Inches Maximum   |
| <b>Width Between Flats:</b>       | 0.304 Inches Minimum And 0.315 Inches Maximum   |
| <b>Extended Washer Diameter:</b>  | 0.428 Inches Minimum And 0.438 Inches Maximum   |
| <b>Extended Washer Thickness:</b> | 0.059 Inches Minimum And 0.079 Inches Maximum   |
| <b>Hole Diameter:</b>             | 0.037 Inches Nominal                            |
| <b>Grip Diameter:</b>             | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| <b>Nominal Thread Diameter:</b>   | 0.250 Inches                                    |
| <b>Grip Length:</b>               | 0.865 Inches Minimum And 0.885 Inches Maximum   |
| <b>Hole Quantity:</b>             | 4   |
| <b>Hole Type:</b>                 | Drilled   |
| <b>Thread Quantity Per Inch:</b>  | 28  |
| <b>Minimum Tensile Strength:</b>  | 200000 Pounds Per Square Inch                   |
| <b>Hole Configuration Style:</b>  | Double Hexagon Longitudinal Hole                |
| <b>Material:</b>                  | Iron Alloy 660 Overall                          |
| <b>Thread Series Designator:</b>  | Unjf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/EWB0420-4H14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.