

**Description**

Fastener Length: 1-29/32", Hole Diameter: ", Thread: 3/4-16, Thread Length: 1-19/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | EWB2212H10                                |
| Minimum Qty (MOQ):      | 1   |
| NSN:                    | 5306-01-048-6084                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N EWB22-12H10 Specifications

|                                     |   |
|-------------------------------------|---|
| <b>Thread Class:</b>                | 3a  |
| <b>Thread Direction:</b>            | Right-hand  |
| <b>Thread Length:</b>               | 1.256 Inches Minimum And 1.306 Inches Maximum                       |
| <b>Fastener Length:</b>             | 1.891 Inches Minimum And 1.921 Inches Maximum                       |
| <b>Head Style:</b>                  | Double Hexagon W/hole   |
| <b>Head Height:</b>                 | 0.806 Inches Nominal  |
| <b>Width Between Flats:</b>         | 0.928 Inches Minimum And 0.940 Inches Maximum                       |
| <b>Extended Washer Diameter:</b>    | 1.415 Inches Minimum And 1.425 Inches Maximum                       |
| <b>Extended Washer Thickness:</b>   | 0.152 Inches Nominal  |
| <b>Hole Diameter:</b>               | 0.055 Inches Nominal  |
| <b>Grip Diameter:</b>               | 0.7480 Inches Minimum And 0.7490 Inches Maximum                     |
| <b>Nominal Thread Diameter:</b>     | 0.750 Inches  |
| <b>Grip Length:</b>                 | 0.615 Inches Minimum And 0.635 Inches Maximum                       |
| <b>Hole Quantity:</b>               | 4   |
| <b>Hole Type:</b>                   | Drilled   |
| <b>Thread Quantity Per Inch:</b>    | 16  |
| <b>Minimum Tensile Strength:</b>    | 220000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>             | 46.0 Rockwell C Minimum Overall And 50.0 Rockwell C Maximum Overall |
| <b>Hole Configuration Style:</b>    | Hexagon Flats   |
| <b>Material:</b>                    | Steel Comp H11 Overall  |
| <b>Surface Treatment:</b>           | Cadmium Overall   |
| <b>Thread Series Designator:</b>    | Unjf  |
| <b>Specification/standard Data:</b> | 92702-fwb22 Manufacturers Standard                                  |

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/EWB22-12H10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.