

Description

Fastener Length: 1-29/32", Hole Diameter: ", Thread: 3/4-16, Thread Length: 1-19/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	EWB2212H10
Minimum Qty (MOQ):	1
NSN:	5306-01-048-6084
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N EWB22-12H10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.256 Inches Minimum And 1.306 Inches Maximum
Fastener Length:	1.891 Inches Minimum And 1.921 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.806 Inches Nominal
Width Between Flats:	0.928 Inches Minimum And 0.940 Inches Maximum
Extended Washer Diameter:	1.415 Inches Minimum And 1.425 Inches Maximum
Extended Washer Thickness:	0.152 Inches Nominal
Hole Diameter:	0.055 Inches Nominal
Grip Diameter:	0.7480 Inches Minimum And 0.7490 Inches Maximum
Nominal Thread Diameter:	0.750 Inches
Grip Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Hardness Rating:	46.0 Rockwell C Minimum Overall And 50.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Flats
Material:	Steel Comp H11 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf
Specification/standard Data:	92702-fwb22 Manufacturers Standard

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/EWB22-12H10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.