

Description

Fastener Length: 2-1/32", Thread: 1/4-24, Thread Length: 1-19/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | EWB22512 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-00-099-8064 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N EWB22-5-12 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.256 Inches Minimum And 1.306 Inches Maximum |
| Fastener Length: | 2.016 Inches Minimum And 2.046 Inches Maximum |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.319 Inches Nominal |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Extended Washer Diameter: | 0.575 Inches Minimum And 0.585 Inches Maximum |
| Extended Washer Thickness: | 0.050 Inches Nominal |
| Grip Diameter: | 0.3110 Inches Minimum And 0.3120 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 0.740 Inches Minimum And 0.760 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 220000 Pounds Per Square Inch |
| Hardness Rating: | 46.0 Rockwell C Minimum Overall And 50.0 Rockwell C Maximum Overall |
| Material: | Steel Comp H11 Overall |
| Material Document And Classification: | Ams 6485 Assn Std Single Material Response Overall Or Ams 6487 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Nas 672 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/EWB22-5-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.