

Description

Fastener Length: 25/32", Hole Diameter: 1/32", Thread: 1/4-28, Thread Length: 35/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	EWB264H4
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-451-5280
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N EWB26-4H4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.506 Inches Minimum And 0.556 Inches Maximum
Fastener Length:	0.766 Inches Minimum And 0.796 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.254 Inches Nominal
Width Between Flats:	0.304 Inches Minimum And 0.313 Inches Maximum
Extended Washer Diameter:	0.465 Inches Minimum And 0.475 Inches Maximum
Extended Washer Thickness:	0.042 Inches Nominal
Hole Diameter:	0.037 Inches Nominal
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	260000 Pounds Per Square Inch
Hardness Rating:	51.0 Rockwell C Minimum Overall And 54.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Longitudinal Hole
Material:	Steel Comp H11 Overall
Material Document And Classification:	Ams 6485 Assn Std Single Material Response Overall Or Ams6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/EWB26-4H4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.