

## **P/N EWB26-4H4**

## **Description**

Fastener Length: 25/32", Hole Diameter: 1/32", Thread: 1/4-28, Thread Length: 35/64"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

| SKU / Model:            | EWB264H4                                  |
|-------------------------|---|
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-00-451-5280                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



<sup>\*</sup> See page 2 for technical characteristics

# **P/N EWB26-4H4 Specifications**

| Thread Class:                         | 3a  |
|---------------------------------------|---|
| Thread Direction:                     | Right-hand  |
| Thread Length:                        | 0.506 Inches Minimum And 0.556 Inches Maximum   |
| Fastener Length:                      | 0.766 Inches Minimum And 0.796 Inches Maximum   |
| Head Style:                           | Double Hexagon W/hole   |
| Head Height:                          | 0.254 Inches Nominal  |
| Width Between Flats:                  | 0.304 Inches Minimum And 0.313 Inches Maximum   |
| Extended Washer Diameter:             | 0.465 Inches Minimum And 0.475 Inches Maximum   |
| Extended Washer Thickness:            | 0.042 Inches Nominal  |
| Hole Diameter:                        | 0.037 Inches Nominal  |
| Grip Diameter:                        | 0.2485 Inches Minimum And 0.2495 Inches Maximum   |
| Nominal Thread Diameter:              | 0.250 Inches  |
| Grip Length:                          | 0.240 Inches Minimum And 0.260 Inches Maximum   |
| Hole Quantity:                        | 4   |
| Hole Type:                            | Drilled   |
| Thread Quantity Per Inch:             | 28  |
| Minimum Tensile Strength:             | 260000 Pounds Per Square Inch   |
| Hardness Rating:                      | 51.0 Rockwell C Minimum Overall And 54.0 Rockwell C Maximum Overall                                     |
| Hole Configuration Style:             | Hexagon Longitudinal Hole   |
| Material:                             | Steel Comp H11 Overall  |
| Material Document And Classification: | Ams 6485 Assn Std Single Material Response Overall Or Ams6487 Assn Std Single Material Response Overall |
| Surface Treatment:                    | Cadmium Overall   |
| Thread Series Designator:             | Unjf  |

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/EWB26-4H4">https://military-fasteners.com/bolts/machine+bolts/EWB26-4H4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.