

Description

Fastener Length: 2-3/8", Thread: 5/8-18, Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | EWSB2210A28 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-00-947-2185 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N EWSB22-10A28 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.632 Inches Minimum |
| Fastener Length: | 2.382 Inches Nominal |
| Head Style: | Double Hexagon |
| Head Height: | 0.350 Inches Nominal |
| Width Between Flats: | 0.928 Inches Minimum And 0.940 Inches Maximum |
| Grip Diameter: | 0.6230 Inches Minimum And 0.6240 Inches Maximum |
| Nominal Thread Diameter: | 0.625 Inches |
| Grip Length: | 1.750 Inches Nominal |
| Thread Quantity Per Inch: | 18 |
| Minimum Tensile Strength: | 220000 Pounds Per Square Inch |
| Hardness Rating: | 46.0 Rockwell C Minimum Overall And 50.0 Rockwell C Maximum Overall |
| Material: | Steel Overall |
| Material Document And Classification: | Sps-m-107,fscm 03680 Mfr Ref Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Nas 672 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/EWSB22-10A28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.