

## **P/N EWSB22-4A7**

## **Description**

Fastener Length: 3/4", Thread: 1/4-28, Thread Length: 21/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: EWSB224A7

Minimum Qty (MOQ): 1 EA

NSN: 5306-00-245-3747

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N EWSB22-4A7 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.267 Inches Minimum And 0.334 Inches Maximum
Fastener Length:	0.714 Inches Minimum And 0.761 Inches Maximum
Head Style:	Double Hexagon
Head Height:	0.154 Inches Minimum And 0.174 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2483 Inches Minimum And 0.2492 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.427 Inches Minimum And 0.447 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Hardness Rating:	46.0 Rockwell C Minimum Overall And 50.0 Rockwell C Maximum Overall
Material:	Steel Comp H11 Overall
Material Document And Classification:	Ams 6485 Assn Std Single Material Response Overall Or Ams 6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	26572-gb511b4 Manufacturers Standard

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/EWSB22-4A7">https://military-fasteners.com/bolts/machine+bolts/EWSB22-4A7</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.