P/N EWSB22-5-12

Description

Fastener Length: 1-3/32", Thread: 1/4-24, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	EWSB22512
Minimum Qty (MOQ):	55 EA
NSN:	5306-00-761-3526
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N EWSB22-5-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.351 Inches Minimum
Fastener Length:	1.101 Inches Nominal
Head Style:	Double Hexagon
Head Height:	0.187 Inches Nominal
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.3108 Inches Minimum And 0.3117 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.750 Inches Nominal
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Hardness Rating:	46.0 Rockwell C Minimum Overall And 50.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.982 Inches Nominal First Hole
Material:	Steel Overall
Material Document And Classification:	Sps-m-107,fscm 03680 Mfr Ref Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	26512-gb511b Manufacturers Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/EWSB22-5-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.