

P/N EWSB22-5-22

Description

Fastener Length: 1-3/4", Thread: 1/4-24, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: EWSB22522

Minimum Qty (MOQ): 1 EA

NSN: 5306-00-119-4700

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N EWSB22-5-22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.242 Inches Minimum And 0.392 Inches Maximum
Fastener Length:	1.710 Inches Minimum And 1.757 Inches Maximum
Head Style:	Double Hexagon
Head Height:	0.177 Inches Minimum And 0.197 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.3100 Inches Minimum And 0.3110 Inches Maximum
Shank Unthreaded Hole Diameter:	0.066 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Nominal Thread Diameter:	0.312 Inches
Grip Length:	1.365 Inches Minimum And 1.385 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	200000 Pounds Per Square Inch
Hardness Rating:	46.0 Rockwell C Minimum Overall And 49.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.497 Inches Minimum First Hole And 1.517 Inches Maximum First Hole
Material:	Steel Overall
Material Document And Classification:	Aics-501 Fscm 06725 Mfr Ref Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	56878-ewsb22 Manufacturers Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/EWSB22-5-22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.