

Description

Fastener Length: 1-3/16", Thread: 3/8-24, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	EWSB226A13
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-948-0642
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N EWSB22-6A13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.400 Inches Minimum
Fastener Length:	1.212 Inches Nominal
Head Style:	Double Hexagon
Head Height:	0.210 Inches Nominal
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.3733 Inches Minimum And 0.3742 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.812 Inches Nominal
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Hardness Rating:	46.0 Rockwell C Minimum Overall And 50.0 Rockwell C Maximum Overall
Material:	Steel Overall
Material Document And Classification:	Sps-m-107,fscm 03680 Mfr Ref Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/EWSB22-6A13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.