



Military-Fasteners.com

P/N EWSB22-7-24

Description

Fastener Length: 1-61/64", Thread: 7/16-20, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	EWSB22724
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-006-9462
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N EWSB22-7-24 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.340 Inches Minimum And 0.507 Inches Maximum
Fastener Length:	1.950 Inches Minimum And 1.997 Inches Maximum
Head Style:	Double Hexagon
Head Height:	0.257 Inches Nominal
Width Between Flats:	0.678 Inches Minimum And 0.689 Inches Maximum
Grip Diameter:	0.4358 Inches Minimum And 0.4367 Inches Maximum
Shank Unthreaded Hole Diameter:	0.105 Inches Nominal First Hole
Nominal Thread Diameter:	0.438 Inches
Grip Length:	1.490 Inches Minimum And 1.510 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Hardness Rating:	46.0 Rockwell C Minimum Overall And 50.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.825 Inches Minimum First Hole And 1.857 Inches Maximum First Hole
Material:	Steel Comp H11 Overall
Material Document And Classification:	Ams6485 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/EWSB22-7-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.