

**Description**

Fastener Length: 1-61/64", Thread: 7/16-20, Thread Length: 11/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	EWSB22724
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-006-9462
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N EWSB22-7-24 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.340 Inches Minimum And 0.507 Inches Maximum
<b>Fastener Length:</b>	1.950 Inches Minimum And 1.997 Inches Maximum
<b>Head Style:</b>	Double Hexagon
<b>Head Height:</b>	0.257 Inches Nominal
<b>Width Between Flats:</b>	0.678 Inches Minimum And 0.689 Inches Maximum
<b>Grip Diameter:</b>	0.4358 Inches Minimum And 0.4367 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.105 Inches Nominal First Hole
<b>Nominal Thread Diameter:</b>	0.438 Inches
<b>Grip Length:</b>	1.490 Inches Minimum And 1.510 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	220000 Pounds Per Square Inch
<b>Hardness Rating:</b>	46.0 Rockwell C Minimum Overall And 50.0 Rockwell C Maximum Overall
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	1.825 Inches Minimum First Hole And 1.857 Inches Maximum First Hole
<b>Material:</b>	Steel Comp H11 Overall
<b>Material Document And Classification:</b>	Ams6485 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Nas 672 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/EWSB22-7-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.