



Military-Fasteners.com

P/N EWSB22-8-28

Description

Fastener Length: 2-17/64", Thread: 1/2-20, Thread Length: 33/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	EWSB22828
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-914-3245
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N EWSB22-8-28 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.518 Inches Minimum
Fastener Length:	2.266 Inches Nominal
Head Style:	Double Hexagon
Head Height:	0.281 Inches Nominal
Width Between Flats:	0.741 Inches Minimum And 0.752 Inches Maximum
Grip Diameter:	0.4982 Inches Minimum And 0.4991 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Nominal First Hole
Nominal Thread Diameter:	0.500 Inches
Grip Length:	1.750 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Hardness Rating:	46.0 Rockwell C Minimum Overall And 50.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.126 Inches Nominal First Hole
Material:	Steel Overall
Material Document And Classification:	Sps-m-107,fscm 03680 Mfr Ref Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/EWSB22-8-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.