

Description

Fastener Length: 2-35/64", Thread: 1/2-20, Thread Length: 35/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	EWSB22832
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-150-3569
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N EWSB22-8-32 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.490 Inches Minimum And 0.557 Inches Maximum
Fastener Length:	2.500 Inches Minimum And 2.547 Inches Maximum
Head Style:	Double Hexagon
Head Height:	0.271 Inches Minimum And 0.291 Inches Maximum
Width Between Flats:	0.741 Inches Minimum And 0.752 Inches Maximum
Grip Diameter:	0.4982 Inches Minimum And 0.4991 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Grip Length:	1.990 Inches Minimum And 2.010 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Hardness Rating:	46.0 Rockwell C Minimum Overall And 50.0 Rockwell C Maximum Overall
Material:	Steel Comp H11 Overall Or Steel Overall
Material Document And Classification:	Ams 6485 Assn Std 1st Material Response Overall Or Ams 6487 Assn Std 1st Material Response Overall Or Sps-m-107 Fscm 56878 Mfr Ref 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	26512-gb511b Manufacturers Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/EWSB22-8-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.