

Description

Thread Size: 1/8", Nut Height: 3/8", Head Width: 3/8", F22K1 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | F22K162 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5310-00-957-1830 |
| Schedule B: | 7318.16.0085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N F22K1-62 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque With Nonmetallic Insert |
| Nut Style: | Cap |
| Nut Height: | 0.337 Inches Nominal |
| Width Across Flats: | 0.365 Inches Minimum And 0.377 Inches Maximum |
| Temp Rating: | 250.0 Deg Fahrenheit Nominal |
| Thread Series: | Unc |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.138 Inches |
| Bearing Surface Type: | Chamfered |
| Material: | Steel Comp 1212 Cap |
| Material: | Steel Comp 1212 Nut |
| Material Document And Classification: | Ams 5010 Assn Std 1st Material Response Nut |
| Material Document And Classification: | Ams 5010 Assn Std 2nd Material Response Cap |
| Surface Treatment: | Cadmium Overall Except Insert |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall Except Insert |
| Specification/standard Data: | 81205-bacn10r Manufacturers Standard |

How to Order

Order this self-locking cap nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+cap+nuts/F22K1-62 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.