

## **P/N F22NKTM-40**

### **Description**

Thread Size: 1/8", Nut Height: 1/4", Head Width: 1/4

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	F22NKTM40
Minimum Qty (MOQ):	5
NSN:	5310-00-816-7866
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N F22NKTM-40 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Nut Style:	Сар
Nut Height:	0.195 Inches Minimum And 0.225 Inches Maximum
Width Across Flats:	0.240 Inches Minimum And 0.252 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Nominal
Thread Series:	Unc
Thread Quantity Per Inch:	40
Nominal Thread Size:	0.112 Inches
Bearing Surface Type:	Washer Faced
Material:	Plastic Polyamide Locking Insert
Material:	Steel Comp 1035 Nut
Material:	Steel Comp 1040 Cap
Material Document And Classification:	Aisi Assn Std 1st Material Response Nut
Material Document And Classification:	Aisi Assn Std 2nd Material Response Cap
Surface Treatment:	Cadmium Nut
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Nut

## **How to Order**

Order this self-locking cap nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+cap+nuts/F22NKTM-40">https://military-fasteners.com/nuts/self\_locking+cap+nuts/F22NKTM-40</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+cap+nuts/F22NKTM-40">https://military-fasteners.com/nuts/self\_locking+cap+nuts/F22NKTM-40</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+cap+nuts/F22NKTM-40">https://military-fasteners.com/nuts/self\_locking+cap+nuts/F22NKTM-40</a> and selecting the