

Description

FHS-032-8 Positive Lock Receptacle

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	FHS0328
Minimum Qty (MOQ):	50
NSN:	5307-01-196-2251
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N FHS-032-8 Specifications

Thread Class:	3a Nut Thread
Thread Direction:	Right-hand Nut Thread
Thread Length:	0.385 Inches Minimum Nut Thread And 0.515 Inches Maximum Nut Thread
Head Diameter:	0.241 Inches Minimum And 0.271 Inches Maximum
Head Length:	0.100 Inches Maximum
Locking Feature:	Self-clinching Head
Overall Length:	0.485 Inches Minimum And 0.515 Inches Maximum
Thread Quantity Per Inch:	32 Nut Thread
Nominal Thread Size:	0.190 Inches Nut Thread
Material:	Steel Comp 301 Or Steel Comp 302 Or Steel Comp 302b Or Steel Comp 303 Or Steel Comp 303se Or Steel Comp 304 Or Steel Comp 304l Or Steel Comp 305 Or Steel Comp 308 Or Steel Comp 309 Or Steel Comp 309s Or Steel Comp 310 Or Steel Comp 310s Or Steel Comp 314 Or Steel Comp 316 Or Steel Comp 316l Or Steel Comp 317 Or Steel Comp 321 Or Steel Comp 347 Or Steel Comp 348 Or Steel Comp 384 Or Steel Comp 385
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	Self-locking
Thread Series Designator:	Unf Nut Thread

How to Order

Order this positive lock receptacle from our inventory online by visiting <https://military-fasteners.com/studs/positive+lock+receptacles/FHS-032-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.