

Description

Fastener Length: 25/32", Thread: 1/4-28, Head Width: 5/32", Thread Length: 35/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	FIT0100034004
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-164-1622
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N FIT01-0003-4004 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.516 Inches Minimum And 0.556 Inches Maximum
Fastener Length:	0.776 Inches Minimum And 0.796 Inches Maximum
Head Style:	Oval Countersunk
Head Diameter:	0.355 Inches Minimum And 0.397 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Width Across Flats:	0.1565 Inches Minimum And 0.1587 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Special Features:	Three Key Slots 0.040 In. Min. And 0.044 In. Max. Dia. Evenly Spaced And 0.681 In. Min. And 0.711 In. Max. Length
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/FIT01-0003-4004> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.