

Description

Fastener Length: 13/32", Thread: 10-32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | FX10150101P |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5305-01-487-1380 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N FX10-15010-1P Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.410 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.520 Inches Minimum And 0.528 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Material Accommodated Thickness: | 0.230 Inches Minimum And 0.290 Inches Maximum |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 100.0 Degrees Nominal |
| Lead Thread Quantity: | Four |
| Material: | Steel Comp 4140 Fastener |
| Material: | Steel Comp 8740 Stand-off |
| Material Document And Classification: | Mil-s-5626 Mil Spec Single Material Response Stand-off |
| Material Document And Classification: | Mil-s-6049 Mil Spec Single Material Response Fastener |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unf |

How to Order

Order this panel screw assembly from our inventory online by visiting <https://military-fasteners.com/studs/panel+screw+assemblies/FX10-15010-1P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.