

**Description**

FX10-15010 series stud

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | FX10150102P                               |
| Minimum Qty (MOQ):      | 1   |
| NSN:                    | 5305-01-387-7396                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N FX10-15010-2P Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Fastener Length:</b>                               | 0.480 Inches Nominal  |
| <b>Head Style:</b>                                    | Flat Countersunk  |
| <b>Head Diameter:</b>                                 | 0.520 Inches Minimum And 0.528 Inches Maximum               |
| <b>Internal Drive Style:</b>                          | Cross Recess Type 1   |
| <b>Material Accommodated Thickness:</b>               | 0.291 Inches Minimum And 0.360 Inches Maximum               |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches  |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch                               |
| <b>Countersink Angle:</b>                             | 100.0 Degrees Nominal                                       |
| <b>Lead Thread Quantity:</b>                          | Four  |
| <b>Material:</b>                                      | Steel Comp 4140 Stand-off                                   |
| <b>Material:</b>                                      | Steel Comp 8740 Fastener                                    |
| <b>Material Document And Classification:</b>          | Mil-s-5626 Mil Spec Single Material Response Stand-off      |
| <b>Material Document And Classification:</b>          | Mil-s-6049 Mil Spec Single Material Response Fastener       |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall                        |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall |
| <b>Thread Series Designator:</b>                      | Unf   |

## How to Order

Order this panel screw assembly from our inventory online by visiting <https://military-fasteners.com/studs/panel+screw+assemblies/FX10-15010-2P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.