

Description

FX10-15010 series stud

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	FX10150102P
Minimum Qty (MOQ):	1
NSN:	5305-01-387-7396
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE
AVAILABLE

P/N FX10-15010-2P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.480 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.520 Inches Minimum And 0.528 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Material Accommodated Thickness:	0.291 Inches Minimum And 0.360 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Lead Thread Quantity:	Four
Material:	Steel Comp 4140 Stand-off
Material:	Steel Comp 8740 Fastener
Material Document And Classification:	Mil-s-5626 Mil Spec Single Material Response Stand-off
Material Document And Classification:	Mil-s-6049 Mil Spec Single Material Response Fastener
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf

How to Order

Order this panel screw assembly from our inventory online by visiting <https://military-fasteners.com/studs/panel+screw+assemblies/FX10-15010-2P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.