

Description

Diameter: 3/8", steel comp 4140 grommet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	FX1015581P
Minimum Qty (MOQ):	5
NSN:	5325-00-759-1770
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N FX10-1558-1P Specifications

Diameter:	0.373 Inches Minimum And 0.375 Inches Maximum
Securing Device Type:	Ring
Turnlock Stud Head Style:	Flat Countersunk
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.410 Inches Nominal
Eyelet Outside Diameter:	0.375 Inches Nominal
Eyelet Length:	0.350 Inches Nominal
Material Accommodated Thickness:	0.150 Inches Minimum And 0.220 Inches Maximum
Drive Type:	Cross Recess
Special Features:	Floating Type
Material:	Steel Comp 302 Ejector Spring
Material:	Steel Comp 4140 Grommet
Material:	Steel Comp 4037 Stud
Surface Treatment:	Cadmium Stud And Chromate Stud
Surface Treatment:	Cadmium Grommet And Chromate Grommet
Surface Treatment:	Passivate Ejector Spring
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Ejector Spring
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Grommet
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Stud

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/FX10-1558-1P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.