

**Description**

Diameter: 3/8", steel comp 4140 grommet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	FX1015581P
Minimum Qty (MOQ):	5
NSN:	5325-00-759-1770
National Motor Freight:	066440, Fasteners Curtain / Snap Metal

NO IMAGE  
AVAILABLE

## P/N FX10-1558-1P Specifications

<b>Diameter:</b>	0.373 Inches Minimum And 0.375 Inches Maximum
<b>Securing Device Type:</b>	Ring
<b>Turnlock Stud Head Style:</b>	Flat Countersunk
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.410 Inches Nominal
<b>Eyelet Outside Diameter:</b>	0.375 Inches Nominal
<b>Eyelet Length:</b>	0.350 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.150 Inches Minimum And 0.220 Inches Maximum
<b>Drive Type:</b>	Cross Recess
<b>Special Features:</b>	Floating Type
<b>Material:</b>	Steel Comp 302 Ejector Spring
<b>Material:</b>	Steel Comp 4140 Grommet
<b>Material:</b>	Steel Comp 4037 Stud
<b>Surface Treatment:</b>	Cadmium Stud And Chromate Stud
<b>Surface Treatment:</b>	Cadmium Grommet And Chromate Grommet
<b>Surface Treatment:</b>	Passivate Ejector Spring
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Ejector Spring
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Grommet
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Stud

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/FX10-1558-1P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.