

Description

Fastener Length: 3-23/32", Thread: 1/2-20, Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	GB511GG8D49A
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-344-6720
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N GB511GG8D49A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.633 Inches Nominal
Fastener Length:	3.679 Inches Minimum And 3.726 Inches Maximum
Head Style:	Double Hexagon
Head Height:	0.271 Inches Minimum And 0.291 Inches Maximum
Width Between Flats:	0.741 Inches Minimum And 0.752 Inches Maximum
Grip Diameter:	0.4990 Inches Minimum And 0.4995 Inches Maximum
Shank Unthreaded Hole Diameter:	0.101 Inches Minimum First Hole And 0.111 Inches Maximum First Hole
Nominal Thread Diameter:	0.500 Inches
Grip Length:	3.062 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	3.496 Inches Nominal First Hole
Surface Finish:	32.0 Microinches Grip
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams 5662 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/GB511GG8D49A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.