

## P/N GN512B3-216

### **Description**

Thread Size: 3/16", Nut Length: 61/64"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: GN512B3216

Minimum Qty (MOQ): 5 EA

NSN: 5310-00-947-7018

Schedule B: 7318.16.0085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N GN512B3-216 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk
Head Diameter:	0.391 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.246 Inches Minimum And 0.250 Inches Maximum
Nut Length:	0.923 Inches Minimum And 0.953 Inches Maximum
Err Default:	+0.166/+0.216 Inches
Shank End Type:	Closed
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Head Countersink Angle:	100.00 Degrees Nominal
Material:	Steel Comp 4037 Overall
Material Document And Classification:	Qq-w-405 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall

## **How to Order**

Order this rivnut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/plain+blind+rivet+nuts/GN512B3-216">https://military-fasteners.com/nuts/plain+blind+rivet+nuts/GN512B3-216</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.