



Military-Fasteners.com

P/N GS551P4-741

Description

Fastener Length: 1-3/64", Thread: 1/4-28, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	GS551P4741
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-151-8658
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N GS551P4-741 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.329 Inches Minimum And 0.389 Inches Maximum
Fastener Length:	1.024 Inches Minimum And 1.054 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.357 Inches Nominal
Grip Diameter:	0.2540 Inches Minimum And 0.2550 Inches Maximum
Internal Drive Style:	Slot
End Item Identification:	W/s: Aircraft, Prowler Ea-6b
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.665 Inches Minimum And 0.695 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	33.0 Rockwell C Minimum Overall
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Color Tan,surface Of Head
Material:	Steel Comp 4037 Overall
Material Document And Classification:	Aisi Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/GS551P4-741> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.