

P/N GS551P4-801

Description

Fastener Length: 1-5/32", Thread: 1/4-28, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: GS551P4801

Minimum Qty (MOQ): 1 EA

NSN: 5305-00-151-8659

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N GS551P4-801 Specifications

| Thread Class: | 2a |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.386 Inches Minimum And 0.446 Inches Maximum |
| Fastener Length: | 1.141 Inches Minimum And 1.171 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.357 Inches Nominal |
| Grip Diameter: | 0.2540 Inches Minimum And 0.2550 Inches Maximum |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.725 Inches Minimum And 0.755 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 150000 Pounds Per Square Inch |
| Hardness Rating: | 33.0 Rockwell C Minimum Overall |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Special Features: | Color Yellow,half Surface Or Head |
| Material: | Steel Comp 4037 Overall |
| Material Document And Classification: | Aisi Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/GS551P4-801 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.