

Description

Fastener Length: 1-5/32", Thread: 1/4-28, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	GS551P4801
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-151-8659
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N GS551P4-801 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.386 Inches Minimum And 0.446 Inches Maximum
Fastener Length:	1.141 Inches Minimum And 1.171 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.357 Inches Nominal
Grip Diameter:	0.2540 Inches Minimum And 0.2550 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.725 Inches Minimum And 0.755 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	150000 Pounds Per Square Inch
Hardness Rating:	33.0 Rockwell C Minimum Overall
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Color Yellow, half Surface Or Head
Material:	Steel Comp 4037 Overall
Material Document And Classification:	Aisi Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/GS551P4-801> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.