

Description

Thread Size: 5/32", Nut Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	H111F2C63070
Minimum Qty (MOQ):	5 EA
NSN:	5310-01-174-3576
Schedule B:	7318.23.0000
ECCN:	9A991



P/N H111F2C63-070 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk
Head Diameter:	0.240 Inches Minimum
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.217 Inches Maximum
Nut Length:	0.405 Inches Minimum And 0.435 Inches Maximum
Err Default:	+0.030/+0.070 Inches
Shank End Type:	Open
Thread Series:	Unjc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Head Countersink Angle:	100.0 Degrees Nominal
Special Features:	Diamond Knurl On Outside
Material:	Steel Comp 303 Overall
Material Document And Classification:	Astm A484 Assn Std Single Material Response Overall Or Astm A582 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this rivet blind insert from our inventory online by visiting <https://military-fasteners.com/inserts/plain+blind+rivet+nuts/H111F2C63-070> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.