

**Description**

Thread Size: 1/8", Nut Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	H111F2C63070M
Minimum Qty (MOQ):	5 EA
NSN:	5310-01-445-7269
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N H111F2C63-070M Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flush
<b>Head Diameter:</b>	0.254 Inches Maximum
<b>Head Height:</b>	0.013 Inches Minimum And 0.019 Inches Maximum
<b>Lubrication:</b>	Dry Film Lubricant
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.217 Inches Maximum
<b>Nut Length:</b>	0.405 Inches Minimum And 0.435 Inches Maximum
<b>Err Default:</b>	+0.030/+0.070 Millimeters
<b>Shank End Type:</b>	Closed
<b>Thread Series:</b>	Unjc
<b>Thread Quantity Per Inch:</b>	A32
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Material:</b>	Steel Comp 303 Overall Or Steel Comp 303se Overall Or Steel Comp 303 Plus X Overall
<b>Material Document And Classification:</b>	Ams 5640 Assn Std All Material Responses Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall

## How to Order

Order this nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/H111F2C63-070M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.