

Description

Thread Size: 1/8", Nut Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	H111F2C63070M
Minimum Qty (MOQ):	5 EA
NSN:	5310-01-445-7269
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N H111F2C63-070M Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flush
Head Diameter:	0.254 Inches Maximum
Head Height:	0.013 Inches Minimum And 0.019 Inches Maximum
Lubrication:	Dry Film Lubricant
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.217 Inches Maximum
Nut Length:	0.405 Inches Minimum And 0.435 Inches Maximum
Err Default:	+0.030/+0.070 Millimeters
Shank End Type:	Closed
Thread Series:	Unjc
Thread Quantity Per Inch:	A32
Nominal Thread Size:	0.164 Inches
Material:	Steel Comp 303 Overall Or Steel Comp 303se Overall Or Steel Comp 303 Plus X Overall
Material Document And Classification:	Ams 5640 Assn Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/H111F2C63-070M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.