

Description

Thread Size: 1/8", Nut Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | H111F2C63070M |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5310-01-445-7269 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N H111F2C63-070M Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Head Style: | Flush |
| Head Diameter: | 0.254 Inches Maximum |
| Head Height: | 0.013 Inches Minimum And 0.019 Inches Maximum |
| Lubrication: | Dry Film Lubricant |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.217 Inches Maximum |
| Nut Length: | 0.405 Inches Minimum And 0.435 Inches Maximum |
| Err Default: | +0.030/+0.070 Millimeters |
| Shank End Type: | Closed |
| Thread Series: | Unjc |
| Thread Quantity Per Inch: | A32 |
| Nominal Thread Size: | 0.164 Inches |
| Material: | Steel Comp 303 Overall Or Steel Comp 303se Overall Or Steel Comp 303 Plus X Overall |
| Material Document And Classification: | Ams 5640 Assn Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |

How to Order

Order this nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/H111F2C63-070M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.