

Description

Length: 1-3/8", cadmium body, HF3 series bearing

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[137-515-9003](#)

SKU / Model:	HF3M
Minimum Qty (MOQ):	1
NSN:	3120-00-913-7982
ECCN:	EAR99
National Motor Freight:	114850, Bearing / Bushing O / T Ball / Roller I / S



P/N HF3M Specifications

Thread Class:	2b
Thread Direction:	Right-hand
Shank Style:	Internally Threaded W/bead And Wrench Flats
Overall Length:	1.3750 Inches Nominal
Bore Diameter:	0.1895 Inches Minimum And 0.1925 Inches Maximum
Outer Member Outside Diameter:	0.6150 Inches Minimum And 0.6250 Inches Maximum
Bore Center To Shank End Distance:	1.0615 Inches Minimum And 1.0625 Inches Maximum
Outer Member Width:	0.2450 Inches Minimum And 0.2500 Inches Maximum
Inner Member Width:	0.3120 Inches Minimum And 0.3125 Inches Maximum
Shank Thread Length:	0.5625 Inches Nominal
Shank Width Across Wrench Flats:	0.3125 Inches Nominal
Thread Diameter:	0.190 Inches Nominal
Thread Quantity Per Inch:	32
Lubrication Feature:	Groove External Inner Member
Material:	Copper Alloy 462 Overall Or Copper Alloy 464 Overall Or Copper Alloy 482 Overall Or Copper Alloy 485 Overall
Surface Treatment:	Cadmium Rod End Body
Style Designator:	Ball Type
Thread Series Designator:	Unf

How to Order

Order this rod end bearing from our inventory online by visiting <https://military-fasteners.com/bearings/rod+end+bearings/HF3M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.