

Description

HL1087-8 Pin-Rivet Collar

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL10878
Minimum Qty (MOQ):	100
NSN:	5320-01-237-3957
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N HL1087-8 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.408 Inches Minimum And 0.412 Inches Maximum
Collar Overall Height:	0.530 Inches Minimum And 0.550 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.272 Inches Minimum And 0.276 Inches Maximum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Collar Style:	Threaded (break Off) Type
Material:	Steel Comp Xm-7 Overall Or Steel Comp 305 Overall
Material Document And Classification:	Astm A493,xm-7 Assn Std 1st Material Response Overall Or Qq-s-763 Fed Spec 2nd Material Response Overall Or Ams 5686 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rievet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rievet+collars/HL1087-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.