

Description

HL1087APBW-5 Pin-Rivet Collar

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL1087APBW5
Minimum Qty (MOQ):	5
NSN:	5320-01-281-6532
Schedule B:	8803.30.0030
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N HL1087APBW-5 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Identification Code Color:	Blue
Collar Outside Diameter:	0.283 Inches Minimum And 0.287 Inches Maximum
Collar Overall Height:	0.415 Inches Minimum And 0.435 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.169 Inches Minimum And 0.173 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Collar Style:	Threaded (break Off) Type
Material:	Steel Comp Xm-7 Body Or Steel Comp 305 Body
Material:	Steel Washer
Material Document And Classification:	Astm A493,ty Xm-7 Assn Std 1st Material Response Collar Or Ams 5686 Assn Std 2nd Material Response Collar Or Qq-s-763 Fed Spec 2nd Material Response Collar
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL1087APBW-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.