

P/N HL1087APBW-5

Description

HL1087APBW-5 Pin-Rivet Collar

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: HL1087APBW5

Minimum Qty (MOQ): 5

NSN: 5320-01-281-6532

Schedule B: 8803.30.0030

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



^{*} See page 2 for technical characteristics

P/N HL1087APBW-5 Specifications

| Thread Class: | 3b |
|--|---|
| Thread Direction: | Right-hand |
| Identification Code Color: | Blue |
| Collar Outside Diameter: | 0.283 Inches Minimum And 0.287 Inches Maximum |
| Collar Overall Height: | 0.415 Inches Minimum And 0.435 Inches Maximum |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Collar Inside Diameter: | 0.169 Inches Minimum And 0.173 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.164 Inches |
| Collar Style: | Threaded (break Off) Type |
| Material: | Steel Comp Xm-7 Body Or Steel Comp 305 Body |
| Material: | Steel Washer |
| Material Document And Classification: | Astm A493,ty Xm-7 Assn Std 1st Material Response Collar Or Ams 5686 Assn Std 2nd Material Response Collar Or Qq-s-763 Fed Spec 2nd Material Response Collar |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Overall |
| Thread Series Designator: | Unjc |

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL1087APBW-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.