

Description

HL10V6-2 Pin-Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL10V62
Minimum Qty (MOQ):	10
NSN:	5320-00-084-0699
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



NO IMAGE
AVAILABLE

P/N HL10V6-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.440 Inches Minimum And 0.460 Inches Maximum
Head Style:	Err-090
Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Width Between Flats:	0.079 Inches Minimum And 0.081 Inches Maximum
Shank Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-riquet, Straight, Threaded
Head Major Diameter:	0.295 Inches Minimum And 0.315 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.130 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-riquet from our inventory online by visiting https://military-fasteners.com/pins/pin_riquets/HL10V6-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.