

Description

HL10V8-5 Pin-Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL10V85
Minimum Qty (MOQ):	5
NSN:	5320-01-225-7797
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



* See page 2 for technical characteristics

P/N HL10V8-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.697 Inches Minimum And 0.717 Inches Maximum
Head Style:	Err-090
Head Height:	0.059 Inches Minimum And 0.069 Inches Maximum
Width Between Flats:	0.0947 Inches Minimum And 0.0967 Inches Maximum
Shank Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Head Major Diameter:	0.387 Inches Minimum And 0.412 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.317 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	95000 Pounds Per Square Inch
Nominal Thread Size:	0.250 Inches
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL10V8-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.