

Description

HL10V8-7 Pin-Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL10V87
Minimum Qty (MOQ):	10
NSN:	5320-01-246-1839
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



P/N HL10V8-7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.823 Inches Minimum And 0.843 Inches Maximum
Head Style:	Err-090
Head Height:	0.059 Inches Minimum And 0.069 Inches Maximum
Width Between Flats:	0.0947 Inches Minimum And 0.0967 Inches Maximum
Shank Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.387 Inches Minimum And 0.412 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
End Item Identification:	Aircraft, Eagle F-15;aircraft, Tomcat F-14;aircraft, Harrier Av-8b;aircraft, Sof (Ac-130h, Mc-130h, Ec-130e, Hc-130);aircraftgalaxy C-5;aircraft, B-1b
Grip Length:	0.443 Inches Maximum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL10V8-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.