

## **P/N HL10VAZ5-10**

## **Description**

Fastener Length: 15/16", Thread Size: 5/32

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

HL10VAZ-05-10 HL10VAZ-5-10

SKU / Model: HL10VAZ510

Minimum Qty (MOQ): 10

NSN: 5320-01-232-9844

Schedule B: 8108.90.3060

ECCN: EAR99

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed



<sup>\*</sup> See page 2 for technical characteristics

# **P/N HL10VAZ5-10 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Identification Code Color:	Black
Fastener Length:	0.927 Inches Minimum And 0.947 Inches Maximum
Head Style:	Err-090
Head Height:	0.037 Inches Minimum And 0.047 Inches Maximum
Width Between Flats:	0.0635 Inches Minimum And 0.0645 Inches Maximum
Shank Diameter:	0.1625 Inches Minimum And 0.1635 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.242 Inches Minimum And 0.262 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.630 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Special Features:	Must Be Installed With A Torque Controlled Hex Key
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Hi-kote 1,294,fscm 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjc

## **How to Order**

Order this pin-rivet from our inventory online by visiting <a href="https://military-fasteners.com/pins/pin\_rivets/HL10VAZ5-10">https://military-fasteners.com/pins/pin\_rivets/HL10VAZ5-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.