

**Description**

protruding shear head, titanium

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL10VAZ54
Minimum Qty (MOQ):	10
NSN:	5320-01-501-7023
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



\* See page 2 for technical characteristics

## P/N HL10VAZ5-4 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Identification Code Color:</b>	Black
<b>Fastener Length:</b>	0.765 Inches Minimum And 0.785 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.037 Inches Minimum And 0.047 Inches Maximum
<b>Width Between Flats:</b>	0.075 Inches Minimum And 0.090 Inches Maximum
<b>Shank Diameter:</b>	0.1625 Inches Minimum And 0.1635 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.242 Inches Minimum And 0.262 Inches Maximum
<b>End Item Identification:</b>	Rq-4a Aircraft
<b>Grip Length:</b>	0.245 Inches Minimum And 0.255 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Part Name Assigned By Controlling Agency:</b>	Protrouding Shear Head
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Material Document And Classification:</b>	Ams 4967 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Aluminum Overall
<b>Surface Treatment Document And Classification:</b>	Hi-shear Spec 294 Mfr Ref Single Treatment Response Overall Or Hi-shear Spec 305 Mfr Ref Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/HL10VAZ5-4](https://military-fasteners.com/rivets/pin_rivets/HL10VAZ5-4) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.