

P/N HL10VAZ5-6

Description

protruding shear head, titanium

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: HL10VAZ56

Minimum Qty (MOQ): 10

NSN: 5320-01-538-0836

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc









^{*} See page 2 for technical characteristics

P/N HL10VAZ5-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.677 Inches Minimum And 0.697 Inches Maximum
Head Height:	0.037 Inches Minimum And 0.047 Inches Maximum
Width Between Flats:	0.063 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.163 Inches Nominal
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.242 Inches Minimum And 0.262 Inches Maximum
Grip Length:	0.370 Inches Minimum And 0.380 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Material:	Titanium Alloy Overall
Surface Treatment:	Aluminum Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL10VAZ5-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/pins/pin_rivets/HL10VAZ5-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/pins/pin_rivets/HL10VAZ5-6 and selecting the quantity you want then click "add to cart".