

Description

protruding shear head, titanium

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL10VAZ56
Minimum Qty (MOQ):	10
NSN:	5320-01-538-0836
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N HL10VAZ5-6 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.677 Inches Minimum And 0.697 Inches Maximum
<b>Head Height:</b>	0.037 Inches Minimum And 0.047 Inches Maximum
<b>Width Between Flats:</b>	0.063 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.163 Inches Nominal
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.242 Inches Minimum And 0.262 Inches Maximum
<b>Grip Length:</b>	0.370 Inches Minimum And 0.380 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Material:</b>	Titanium Alloy Overall
<b>Surface Treatment:</b>	Aluminum Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL10VAZ5-6](https://military-fasteners.com/pins/pin_rivets/HL10VAZ5-6) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.