

P/N HL10VAZ6-2

Military-Fasteners.com

Description

Diameter: 3/16", Grip Length: 1/8", protruding shear head, titanium

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	HL10VAZ62
Minimum Qty (MOQ):	20
NSN:	5320-00-338-5674
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



P/N HL10VAZ6-2 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Fastener Length:	0.440 Inches Minimum And 0.460 Inches Maximum
Head Style:	Err-090
Head Height:	0.044 Inches Minimum And 0.055 Inches Maximum
Width Between Flats:	0.079 Inches Minimum And 0.081 Inches Maximum
Shank Diameter:	0.189 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.295 Inches Minimum And 0.315 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.130 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	294,fscm 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting <u>https://military-fasteners.com/pins/pin_rivets/HL10VAZ6-2</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.