

Description

protruding shear head, titanium

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL10VAZ64
Minimum Qty (MOQ):	10
NSN:	5320-01-501-7019
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



P/N HL10VAZ6-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Identification Code Color:	Black
Fastener Length:	0.765 Inches Minimum And 0.785 Inches Maximum
Head Style:	Err-090
Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Width Between Flats:	0.104 Inches Minimum And 0.119 Inches Maximum
Shank Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.295 Inches Minimum And 0.315 Inches Maximum
End Item Identification:	Rq-4a Aircraft
Grip Length:	0.245 Inches Minimum And 0.255 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Part Name Assigned By Controlling Agency:	Protrouding Shear Head
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Hi-shear Spec 294 Mfr Ref Single Treatment Response Overall Or Hi-shear Spec 305 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL10VAZ6-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.