

P/N HL10VF-6-4

Description

5320-01-156-7805 Pin-rivet

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	HL10VF64
Minimum Qty (MOQ):	5
NSN:	5320-01-156-7805
ECCN:	EAR99



^{*} See page 2 for technical characteristics

P/N HL10VF-6-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.565 Inches Minimum And 0.585 Inches Maximum
Head Style:	Err-090
Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Shank Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.295 Inches Minimum And 0.315 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.255 Inches Maximum
Nominal Thread Size:	0.190 Inches
Shear Strength:	5380 Double Pounds Per Square Inch
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL10VF-6-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.