

Description

5320-01-156-7805 Pin-rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | HL10VF64 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5320-01-156-7805 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N HL10VF-6-4 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.565 Inches Minimum And 0.585 Inches Maximum |
| Head Style: | Err-090 |
| Head Height: | 0.045 Inches Minimum And 0.055 Inches Maximum |
| Width Between Flats: | 0.0791 Inches Minimum And 0.0806 Inches Maximum |
| Shank Diameter: | 0.1890 Inches Minimum And 0.1895 Inches Maximum |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.295 Inches Minimum And 0.315 Inches Maximum |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Grip Length: | 0.255 Inches Maximum |
| Nominal Thread Size: | 0.190 Inches |
| Shear Strength: | 5380 Double Pounds Per Square Inch |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL10VF-6-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.