

Description

Fastener Length: 41/64", Thread Size: 3/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL10VF65
Minimum Qty (MOQ):	15
NSN:	5320-01-147-6094
Schedule B:	8108.90.3060
ECCN:	EAR99



* See page 2 for technical characteristics

P/N HL10VF6-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Identification Code Color:	Blue
Fastener Length:	0.627 Inches Minimum And 0.647 Inches Maximum
Head Style:	Err-090
Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Width Between Flats:	0.079 Inches Minimum And 0.081 Inches Maximum
Shank Diameter:	0.188 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.295 Inches Minimum And 0.315 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Unable To Decode:	Unable To Decode
Grip Length:	0.307 Inches Minimum And 0.317 Inches Maximum
Nominal Thread Size:	0.190 Inches
Shear Strength:	5380 Double Pounds Per Square Inch
Special Features:	U/w Collars Hl70,hl79,hl82,hl94k,hl94v,hl97k,hl97v,hl379v And Hl379sy
Heat Treatment:	As Fabricated Overall
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Surface Treatment Document And Classification:	Spec 306,type 1,color Blue Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	73197-hl10 Manufacturers Standard

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL10VF6-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.